

## PULVERIZED ACTIVATED CARBON FILTER CARTRIDGE

- Composed of pre-washed, finely pulverized activated carbon, encapsulated in a depth filtration media of highly purified alpha-cellulose and synthetic fibers for removing chlorine
- Depth-type cartridge ensures superior dirt holding capacity in sediment-laden waters to minimize premature exhaustion while it is being carbon treated
- Design includes a thermally bonded outer, nominal 10 micron pre-filtration layer that provides for depth filtration in one pass without carbon channeling or media migration



### CARTRIDGE SPECIFICATIONS

Dimensions	10" Cartridge	20" Cartridge
Diameter (OD)	2.75" (7.0 cm)	2.75" (7.0 cm)
Length/in (cm)	9.75" (24.8 cm)	20"(50.8 cm)
<b>Recommended Water Flow Rates</b>		
Maximum	1.0 gpm (3.8 lpi)	2.0 gpm (7.6 lpm)
<b>Materials</b>		
Primary Filter Media	Pulverized, Activated Carbon	
Inner Layer Media	Alpha Cellulose and Synthetic Fibers	
Inner Core	Polypropylene	
Outer Netting	Polyolefin	
End Caps	Low Durometer Polyethylene	
<b>Operating Parameters</b>		
Temperature Range	32 to 125°F (0 - 52°C)	
<b>Carbon Volume</b>		
	3.7 ounces of pulverized carbon per 10" length	

### ORDERING INFORMATION

Catalog Number and Description	
<b>FCPC</b>	<b>Filter Cartridge Pulverized Carbon</b>
<b>F</b>	Cartridge Code: <b>F</b> = double open end w/flat gasket seal)
<b>XX</b>	Length (in): <b>10</b> = 10, <b>20</b> = 20
<b>10</b>	Nominal micron retention rating

To figure your order number, replace the X with one of the numbered or lettered options beside it. Note: Not all part number combinations are available; consult Technical Support for assistance.