


VARIABLE INLET AND OUTLET ORIENTATIONS CAN BE CONFIGURED USING PROVIDED ADAPTERS AND PLUGS

REFER TO OPERATIONAL MANUAL OR SIEMENS IONPURE SUPPORT FOR ADDITOINAL INFORMATION




PRODUCT PORT LABELS BLUE

INLET

OUTLET




INLET OU



1 1/2 INCH PVC FEMALE PIPE ADAPTER FOUR PROVIDED PART NUMBER W2T271842

DETAIL A SHOWING THREE METHODS OF SEALING WITH NEW GASKET


VNX 50-2 (OLDER MODEL)





Siemens proudly announces the next advancement in lonpure® CEDI technology. First launched in 2004, the VNX module has quickly become the standard in high flow systems for Power and Microelectronics. Through continued process and technical improvements the current module further improves performance and reduces installation requirements and cost.

- Use VNX 55-2 for improved performance or increased flow capability. To replace with equal flow/performance see VNX 50-3.
- The new VNX 55-2 increases flow capability by 10% to 55 GPM [12.5 m³/ h].
- Updated internal sealing with through-port Endblock gaskets.
- Common electrical and process connection layout.
- All dimensions given in Inches, followed by Centimeters in brackets.


VNX 55-2 (2013 MODEL)







JUNCTION BOX END FOUR PLUGS PROVIDED



COMMON JUNCTION BOX FOR BOTH 50-2 AND 55-2



NED S ION SER IS D. F. ENT END ES D. F. ENT END ES D. F. ENT END ES D. F. ENT.	DESIGNER H.FRYE	DATE 1/23/13	TITLE			_	
	CHECKER	DATE	VNX 50-2 VS. VNX 55-2				
	ENGINEER	DATE					
	MANAGER	DATE	SIEN	1ENS	IONPURE LOWELL, I	PRODUCTS MA	
	FILE: 50-2 TO 55-2 RB		PROJECT	FORMAT	DRAWING	SHEET	RE\
	SCALE: NA		RD3002	22X34 D	50-2 TO 55-2	1 OF 1	В