

# **VANTAGE® PTC CARBON FILTERS**

Vantage® PTC carbon filters for commercial applications offer a flexible, reliable and feature-rich solution to remove Chlorine and Chloramines. They also reduce organics from your feed water - substances that are harmful to RO membranes and other sensitive downstream devices.

Carbon filter vessel diameters range from 10" (25.4cm) to 48" (122cm). Each carbon filter contains acid washed granular activated carbon media.

Vantage PTC carbon filters are available in three models: Economy, Plus, and Deluxe.

- Economy Controlled by a digital controller and composite valve
- Plus Controlled by mechanical time clock and a lead free brass valve
- Deluxe Controlled by a feature-rich digital controller and a lead free brass valve

The Deluxe models are available in four vessel configurations: Simplex, Duplex, Triplex and Quadplex.

Deluxe models are available in three Operational Flow configurations depending on the number of vessels.

- Simplex Operation single vessel operation
- Parallel all vessels (2-4) working together
- X + N two, three or four vessels working together as flow increases and then vessels are placed in stand-by as flow decreases.

## **VANTAGE PTC SYSTEM FEATURES**

- Optional differential pressure switch
- 24vac systems with UL® & cUL® Listed transformers
- Feature-rich digital controller for networked systems
- Tanks and valves are NSF/WQA\* approved
- Corrosion-resistant fiberglass vessels

#### **VANTAGE PTC SYSTEM BENEFITS**

- Minimizes backwash and water usage while maximizing duration between backwashes
- Complies with regulatory and safety requirements
- Offers maximum operational flow and configuration flexibility to the customer
- Requires stringent testing for leaching of contaminates, providing a safe system
- Prevents rust and increases longevity of the vessel

\* NSF = National Science Foundation WQA = Water Quality Association Deluxe models are also available with a side mount valve configuration on the 36", 42" and 48" diameter vessels.

- Minimizes climbing up a ladder to service the valve, enhancing safety
- Provides for more even flow through the Media Bed on larger diameter vessels

The Economy and Plus models will only operate in the following flows:

Simplex Operation - single vessel operation. Multiple simplex units may be purchased to work together, however they will not function as one system as with the Deluxe model. A system lockout is available.

#### **NOMINAL DESIGN PARAMETERS**

Configurations	Simplex, Duplex, Triplex or Quadplex				
Inlet Pressure	30 psig minimum				
Inlet Temperature	65° F				
Sizing	1-3 gpm/ft <sup>3</sup>				
Bed Depth*	35 to 49 inches				
Freeboard	33 to 45% of tank volume				
Backwash	12.8 gpm/ft²				

#### **SPECIFICATIONS \***

Carbon Filter	Vessel Diameter	Media Height (inches)	Media Volume (ft³)	Min Flow Rate (.5 gpm ft³)	Nominal Flow Rate Chloramine Removal (.75 gpm ft³)	Nominal Flow Rate TOC Removal (1 gpm ft <sup>3</sup> )	Nominal Flow Rate Chlorine Removal (3 gpm ft <sup>3</sup> )	Temporary Max Flow Rate (6 gpm ft³)	Economy Valve size	Plus & Deluxe Valve Size options
PTCCS_xx10X54	10	37	1.7	1.1	1.1	1.5	4.5	9.0	1"	1"
PTCCS_xx12X52	12	35	2.3	1.6	1.5	2.0	6.0	12.0	1"	1"
PTCCS_xx14X65	14	38	3.4	2.1	2.3	3.0	9.0	18.0	1"	1" / 1.5"
PTCCS_xx16X65	16	40	4.6	2.8	3.0	4.0	12.0	24.0	1"	1" / 1.5"
PTCCS_xx18X65	18	46	6.8	3.5	4.5	6.0	18.0	36.0	1.5"	1.5" / 2"
PTCCS_xx21X62	21	45	9.0	4.8	6.0	8.0	24.0	48.0	N/A	1.5" / 2"
PTCCS_xx24X65	24	49	12.8	6.3	8.3	11.0	33.0	66.0	N/A	1.5" / 2"
PTCCS_xx30X72	30	48	19.8	9.8	12.8	17.0	51.0	102.0	N/A	2" / 3"
PTCCS_xx36X72	36	48	28.0	14.1	18.0	24.0	72.0	144.0	N/A	2" / 3"
PTCCS_xx42X72	42	46	36.5	19.2	24.0	32.0	96.0	192.0	N/A	3"
PTCCS_xx48X72	48	46	48.5	25.1	31.5	42.0	126.0	252.0	N/A	3"

<sup>\*</sup> Flow rates can vary based on Valve Size and Trim Package selected

# **EVOQUA WATER TECHNOLOGIES IS A LEADER IN THE WATER TREATMENT SERVICE INDUSTRY**

A customizable contract allows you to decide the level and frequency that is best for your facility. Our trained and certified field service technicians are ready to partner with you for your success.

## **SOFTENER SERVICES AVAILABLE:**

- Annual Service Contracts
  WaterComplete<sup>™</sup> Contracting Services
  Water One<sup>®</sup> Service Contracts



210 Sixth Avenue, Suite 3300, Pittsburgh, PA 15222

Technical Support +1 (800) 875-7873 ext 5000

24/7 Customer Service +1 (800) 466-7873

www.evoqua.com

Vantage, WaterComplete and Water One are trademarks of Evoqua, its subsidiaries or affiliates, in some countries. UL and cUL are trademarks of UL LLC.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.